

# VIDEO KIT 4 INPUTS 7" OR 9"

## • COMPLETE AND EASY-TO-USE EQUIPMENT

Available in 7" or 9", the screen offers a clear and contrasted image for optimal visibility. You can connect up to 4 cameras. Split screen mode gives you a complete view of your cameras



- 7" ou 9"
- AUTO (AV1, AV2, AV3, AV4)
- 9 MODES (AV1, AV2, AV3, AV4)
- IP40 screen
- COLOR
- TRIGGER AV1, AV2, AV3, AV4
- 12>24 VOLTS
- IP69K camera
- +70°C / -20°C
- Speaker icon

## • PICTURE QUALITY



Night vision



Facing the sun

v02-042019

# VIDEO KIT 4 INPUTS 7" OR 9"

## CAMERA

Item code : VICAM-AMS-CAM-PAL



### Features :

- Protection rating against solids and liquids : IP69K
- Operating temperature : -20°C +70°C
- Storage temperature : -30°C +80°C
- VGA : 976 x 582 pixels
- Integrated heating
- Night vision
- Night vision distance : 13.5 m
- Excellent vision even facing the sun
- Mirror function integrated in the camera

18 LED IR	IP69K	MICROPHONE	700 TVL	12 VOLTS	120°	CCD 1/3 SONY
PAL	+70°C -20°C	EMA AMS	20°	±15M	L: 97 W: 89 D: 77 (MM)	

## SCREEN

Item code MS7 : VICAM-AMS-MS7-12V

Item code MS9 : VICAM-AMS-MS9-12V



### Features :

- Possibility to connect up to 4 cameras
- High resolution 7" or 9" (16:9) LCD color screen with intermittent timing and split screen mode
- Anti-reflecting screen
- Operating temperature : -20°C <+70°C
- Adjustable luminosity, color and contrast
- Inversion of the horizontal and vertical image
- Resolution : 800 x 3 (RGB) x 480 pixels
- Adjustable and removable stand

7" / 9"	AV1 AV2 AV3 AV4 AUTO	AV1 AV2 AV3 AV4 9 MODES	IP40	COLOR	SPEAKER	BATTERY	EMA AMS
AMS MIRROR	12>24 VOLTS	PAL NTSC	TRIGGER AV1 AV2 / AV3 / AV4	+70°C -20°C	M7 L : 181 W : 128 D : 37 (MM)	M9 L : 234 W : 158 D : 38 (MM)	

v02-042019